Document No: B863CTL Edition: 1

 Date:
 2019-07-30

 Page:
 1(1)

 Prepared:
 AP

 Approved:
 MS

ALO Center AB Industrivägen 10 SE-792 32 Mora Sweden +46 250 94900 info@alocenter.se

www.alocenter.se



ALO 863-CTL

ALO 863-CTL

Heavy duty electrical powered band saw coiler



An electrical coiler for heavy duty service built to manage the bigger and heavier band saw coils. The coiling plate have machined slots to facilitate bundling and loading/un-loading coils with hoist equipment or similar.

The coiler have pneumatically controlled safety casing around the coiling plate that can be lowered when loading or unloading coils.

An electric motor with integrated frequency control as regulated in combination with a band holder arm and a speed regulation arm ensures a very even and smooth operation, no matter if it operates with an ALO machine or as an "standalone" installation.

ALO 863-CTL has a pushbutton panel mounted on the stand with functions for emergency stop, jog function and direction selection - clockwise winding (CCW) or counterclockwise winding (CCW).

Several different expandable coiling center's including auto band end locking device are available as option.

SELECT:

ALO 90915/90916/90917/90918

Expandable centre with auto band lock

 Coil center
 Expanded size

 90915
 320 mm

 90916
 450 mm

 90917
 500 mm

 90918
 400 mm



Expanded center



Collapsed center

TECHNICAL SPECIFICATION:

Drive motor system: Electric, frequency controlled motor

Coiler OD: 1250 mm
Size from floor to band back: 1100 mm
Air pressure: 5 bar

Space requirement(I x w x h): 1430 x 2235x 1315mm

Machine weight:

Max coiler load weight:

480 kg

250 kg

Standard voltage: 400VAC ±10% 3-phase, 50-60 Hz ±1% directly earthed

system, other voltages available upon request.



